

# 150 Speedster®

A rocket on water with intuitive handling and intense maneuverability. All driven by 2 choices of Rotax® 4-TEC® engines.

MUSCLECRAFT | 2011



Yellow



## CLCS Specifications

### DIMENSIONS

Length	15' 4" / 4.67 m
Beam	7' 1" / 2.16 m
Draft	12" / 30.5 cm
Dry weight	1,454 lb. / 659 kg
Seating capacity	4
Fuel capacity	21 gal. / 79.4 l

### ENGINE

Model	1503 Rotax 4-TEC
Type	1.5 l injected or 1.5 l high output

## Highlights

- 1.5 l injected or 1.5 l high output Rotax 4-TEC engine
- Digital Information Center with 18 functions including depth finder, compass, water temperature, hour meter
- Satellite-ready stereo with MP3 port and 2 speakers
- Chrome cleats (4)
- Non-slip grab handles (8)
- Driver console
- Front and stern lockable storage
- Ski pylon – pull-up
- Swim platform with ladder



Digital information center



Sporty seats



Satellite-ready stereo with MP3 port



Lockable stern storage

# 150 Speedster

MUSCLECRAFT | 2011



Red

## Overall Specifications

### DIMENSIONS

Length	15' 4" / 4.67 m
Beam	7' 1" / 2.16 m
Draft	12" / 30.5 cm
Dry weight	1,454 lb. / 659 kg
Storage capacity	14.5 cu. ft. / .44 cu m
Seating capacity	4
Weight capacity	715 lb. / 324 kg
Fuel capacity	21 gal. / 79.4 l

### DIMENSIONS (ON TRAILER)

Length	18' 5" / 5.6 m
Width	7' 1" / 2.16 m
Height: No tower	4' 11" / 1.50 m
Tower down	6' 10" / 2.08 m
Tower up	8' 6" / 2.59 m
Gross weight	2,100 lb. / 952 kg

### ENGINE

Model	Fuel injected, 1503 Rotax 4-TEC
Displacement	1,494 cc
Type: Std.	1.5 l injected
Opt	1.5 l high output
Cylinders	3
Max RPM: 1.5 l injected	7,300
1.5 l high output	8,000
Octane: Minimum	87
Recommended (1.5 l high output)	91
Emission level	CARB 3-Star
Cooling system	Closed-Loop Cooling System

### ELECTRICAL

Generator	30 amp / 380 W
Battery	12 V

### HULL & DECK

Material	Composite FRP
Vinylester barrier layer	Std
Full fiberglass stringer	Std
Graphics	Std
Deadrise	20°
Colors	Yellow
	Red

### PROPULSION

Jet pump type:	
Axial flow	Single stage
Pump diameter: 1.5 l injected	6 1/8" / 15.56 cm
1.5 l high output	6 1/4" / 15.63 cm
Impeller:	
Material	Stainless steel
Outside diameter (mm) 1.5 l injected	155 ± .07
1.5 l high output	159 ± .07
Reverse system	Std

## Equipment

### HULL & DECK

- Cleats – chrome (4)
- Cup holders (4)
- Rub rail – Black
- Grab handles (8)
- Non-skid decking
- Navigation lights
- Ski pylon – pull-up
- Tow hooks – stainless steel bow & stern
- Walk-through – bow
- Reboarding ladder – stern (1-step)
- Engine access – sunpad
- Engine blower
- Auto bilge pump

### STORAGE

- In-floor, lockable
- Sunpad, lockable
- Console, lockable – starboard

### CONTROL STATION

#### HELM

- Steering – standard
- Separated shift & throttle lever
- **Neutral lock\***
- Battery switch
- Fuse box
- Security system D.E.S.S. magnetic lanyard key

### CONTROL STATION (Cont'd)

#### INSTRUMENTATION

- Fuel level
- Tachometer
- Speedometer
- Hour meter
- Maintenance info
- Compass
- Water temperature
- Depth finder
- Low fuel level
- Low oil level
- Low oil pressure
- Low voltage
- Overheat
- Hi voltage
- Check engine
- Sensor check
- Battery protection
- Key (Wrong Key)

### COCKPIT

- Dash finish – Black
- Outlet – 12 volt accessory (1)
- Cooler – integrated

### STEREO & SOUND

- Stereo system – satellite-ready
- Speakers – cockpit (2)
- MP3 port

### CANVAS & MISCELLANEOUS

- Sunpad
- Warranty (1 yr)

### CERTIFICATIONS

- NMMA
- CMMA

### TRAILER

- Single axle

## Options

- Wakeboard tower & racks
- Carpet – snap-in
- Mirror – with tower only
- Mooring cover
- Bimini top (incl. with tower)
- Galvanized trailer
- Fire extinguisher
- Anchor
- Warranty – B.E.S.T. (3 years)



\*New for 2011

